

**PART NUMBER - VALVE SELECTION**

Series	Size	-	Base Code	Body	Ball/ Stem	Seats	Seals	-	Service Mod	Ball Mod	-	Special Features
15	0400	-	11002	S	S	J	G	-	N	N	-	
1	2	-	3	4	5	6	7	-	8	9	-	10

Example:150400-11002SSJG-NN = 4" F30, Full Port, ANSI 300 RF Flanged Ends, Stainless Steel Body, Ball and Stem, TFM 1600 Seats, Graphite Seals.

<b>1</b>	<b>Series</b>	15	Flanged Series - Floating Ball Valves	<a href="#">Website Link</a>
----------	---------------	----	---------------------------------------	------------------------------

<b>2</b>	<b>Size</b>	0050	1/2" (Full Port Only)	0200	2"	0600	6"
		0075	3/4" (Full Port Only)	0250	2-1/2" (Full Port Only)	0800	8"
		0100	1"	0300	3"	1000	10"
		0150	1-1/2"	0400	4"	1200	12"

-	-
---	---

<b>3</b>	<b>Base Code (Model)</b>	11000	F15 - Full Port - ANSI 150 RF Flanged Ends	11001	RF15 - Standard Port - ANSI 150 RF Flanged Ends
		11002	F30 - Full Port - ANSI 300 RF Flanged Ends	11021	RF30 - Standard Port - ANSI 300 RF Flanged Ends
			<a href="#">F15 / F30 Website Link</a> <a href="#">F15 / F30 Brochure</a>		<a href="#">RF15 / RF30 Website Link</a> <a href="#">RF15 / RF30 Brochure</a>

<b>4</b>	<b>Body</b>	S	316 Stainless Steel	A	Alloy 20
		C	WCB Carbon Steel	?	Special Materials (Consult Factory)

<b>5</b>	<b>Ball &amp; Stem</b>	S	316 Stainless Steel Ball with 316 Stainless Steel Stem	D	316 Stainless Steel Ball with 17-4 SS Stem
				A	Alloy 20 Ball and Alloy 20 Stem

<b>6</b>	<b>Seats</b>	J	TFM 1600	U	UHMWPE
		K	Tek-Fil	P	PEEK*
		R	RPTFE	T	PTFE

<b>7</b>	<b>Seals</b>	G	Graphite	U	UHMWPE
		R	RPTFE	K	Tek-Fil
		J	TFM 1600	T	PTFE

-	-
---	---

<b>8</b>	<b>Service Modification</b>	N	None	X	Oxygen Cleaning
		C	General Cleaning	M	NACE MRO 175 2003 (Upgraded Bolting - F15/F30)

<b>9</b>	<b>Ball Modification</b>	N	None	H	Vented Ball
----------	--------------------------	---	------	---	-------------

-	-
---	---

<b>10</b>	<b>Special Features (Optional)</b>	0001	Cavity Fillers	0031	Polished 10-15 Ra	0055	Special Trust Washer Material
		0009	Polished to 30-35 Ra	0210	Polished 8-12 Ra	????	Consult Factory
		0032	Polished to 20-25 Ra				

**NOTES:**

15 Series Valves come standard with a Lockable Lever. Recommended to add a Gear Operator for 6" Full Port and up.

Not all sizes are available in Standard Port (RF15/RF30) Models - See price pages

\*17-4 Stem is Required when using PEEK seats

Stainless Steel Spiral Wound Graphite Body Seal is standard on F15/F30 unless otherwise requested.

Flat Face Flanged Ends or RTJ Flanged Ends are available on request.

General Cleaning per Flow-Tek WI-125 (solvent method) & Bagged meets ASME BPE-2002A

Cavity Fillers only Available in F15 and F30 Models

Special Materials of Construction are available on request.